



SAFETY DATA SHEET FLOOR GRIP RESIN.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name FLOOR GRIP RESIN.
Product No. X0035

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier ITW DEVCON
BAY 150
SHANNON INDUSTRIAL ESTATE
SHANNON
CO CLARE
IRELAND
T: +353 (0)61471299
F: 353(0)61471285
info@itwippe.eu

1.4. Emergency telephone number

+44 (0) 1235 239670

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Xi;R36/38. R43. N;R51/53.

2.2. Label elements

Contains EPOXY RESIN (Number average MW <= 700)
OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS

Labelling



Irritant



Dangerous for the environment

Risk Phrases

R43 May cause sensitisation by skin contact.
R36/38 Irritating to eyes and skin.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrases

S24/25 Avoid contact with skin and eyes.
S37/39 Wear suitable gloves and eye/face protection.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28 After contact with skin, wash immediately with plenty of water.
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.
P5 Contains epoxy constituents. See information supplied by the manufacturer.

2.3. Other hazards

FLOOR GRIP RESIN.

This product does not contain any PBT or vPvB substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ACRYLATE COPOLYMER	< 1%
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
CARBON BLACK	1-5%
CAS-No.: 1333-86-4	EC No.:
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
EPOXY RESIN (Number average MW <= 700)	30-60%
CAS-No.: 25068-38-6	EC No.: 500-033-5
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC) R43 Xi;R36/38 N;R51/53
ORGANOCLAY	1-5%
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) R52/53.
OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS	10-30%
CAS-No.: 68609-97-2	EC No.:
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Skin Sens. 1 - H317	Classification (67/548/EEC) R43 Xi;R38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen. Contact physician if discomfort continues.

Ingestion

Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Drink plenty of water. Get medical attention.

FLOOR GRIP RESIN.

Skin contact

Remove affected person from source of contamination. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation persists.

Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards

When heated and in case of fire, irritating vapours/gases may be formed.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Absorb with sand or other inert absorbent. Transfer to a container for disposal. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only in well-ventilated areas. Keep away from heat, sparks and open flame. Handle and open container with care. Observe good chemical hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Ingredient Comments

No exposure limits noted for ingredient(s).

FLOOR GRIP RESIN.

8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash, quick drench.

Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

Use protective gloves made of: Rubber or plastic.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving work place.

Skin protection

Avoid contact with skin.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Black.
Odour	Slight odour.
Solubility	Slightly soluble in water.
Initial boiling point and boiling range	>260
Melting point (°C)	N/D
Relative density	1.1-1.3 20 °C
Vapour density (air=1)	>1
Vapour pressure	0.03mmHg 77.2
Evaporation rate	<1(Butyl Acetate =1)
pH-Value, Conc. Solution	7.0 @ 20 °C
Viscosity	6000 25
Flash point (°C)	> 204
Auto Ignition Temperature (°C)	>300

9.2. Other information

Not available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Strong oxidising agents. Acids. Amines. Organic peroxides/hydroperoxides.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Hazardous Polymerisation

Will not polymerise.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

FLOOR GRIP RESIN.

10.5. Incompatible materials

Materials To Avoid

Avoid contact with: Strong oxidising agents. Strong acids. Amines. Organic peroxides/hydroperoxides. Inorganic peroxides. Bases, alkalis (organic).

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Acids - organic. Aldehydes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Skin contact

Irritating to skin. May cause sensitisation by skin contact. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

Eye contact

Irritating to eyes.

Health Warnings

Preparation contains an epoxy resin, which may cause sensitisation and development of allergy.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Name	EPOXY RESIN (Number average MW <= 700)
Toxic Dose 1 - LD 50	>2000 mg/kg (oral rat)
Toxic Dose 2 - LD 50	>2000 mg/kg (oral rat)
Name	ACRYLATE COPOLYMER

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment. Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute Fish Toxicity

Very toxic to aquatic organisms.

12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

Do not allow ANY environmental contamination. Do not discharge into drains, water courses or onto the ground.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

Waste Class

08 04 99

FLOOR GRIP RESIN.

SECTION 14: TRANSPORT INFORMATION

General No other information noted.

14.1. UN number

UN No. (ADR/RID/ADN) 3082
UN No. (IMDG) 3082
UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

14.3. Transport hazard class(es)

ADR/RID/ADN Class 9
ADR/RID/ADN Class Class 9: Miscellaneous dangerous substances and articles.
ADR Label No. 9
IMDG Class 9
ICAO Class/Division 9
Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group III
IMDG Packing group III
ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



14.6. Special precautions for user

EMS F-A, S-F
Emergency Action Code •3Z
Hazard No. (ADR) 90
Tunnel Restriction Code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information required.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Water hazard classification

WGK 2

FLOOR GRIP RESIN.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Date	12/08/2011
Revision	12
Supersedes date	22/12/2009
Date	26/07/2011
Risk Phrases In Full	
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard Statements In Full	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.