

ITW Engineered Polymers

SAFETY DATA SHEET WEAR RESISTANT LIQUID (WR) RESIN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name WEAR RESISTANT LIQUID (WR) RESIN
Product number X0012

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Engineered Polymers
Bay 150
Shannon Industrial Estate
Shannon
Co. Clare

+353 (0)61 471 299
+353 (0)61 471 285
mail@itwep.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43. N;R51/53.

Human health The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.

2.2. Label elements

Pictogram



Signal word

Warning

WEAR RESISTANT LIQUID (WR) RESIN

Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	EPOXY RESIN (Number average MW <= 700)
Supplementary precautionary statements	P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Number average MW <= 700)			30-60%
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-0000	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53		
Eye Irrit. 2 - H319			
Skin Sens. 1 - H317			
Aquatic Chronic 2 - H411			
TITANIUM DIOXIDE			1-5%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-0000	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Not Classified	-		
SILICA SAND			<1%
CAS number: 14808-60-7	EC number: 238-878-4		
Classification	Classification (67/548/EEC or 1999/45/EC)		
Not Classified	-		

WEAR RESISTANT LIQUID (WR) RESIN

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
Skin contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

WEAR RESISTANT LIQUID (WR) RESIN

Usage precautions

Use only in well-ventilated areas. Handle and open container with care. Provide adequate ventilation. Keep away from heat, sparks and open flame. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using the product. Do not use in confined spaces without adequate ventilation and/or respirator.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): 10 mg/m³ total dust

SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0.3 mg/m³ Resp Dust, HK

WEL = Workplace Exposure Limit

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL

Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day

Workers - Inhalation; Short term systemic effects: 12.25 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Rubber or plastic. It is recommended that gloves are made of the following material: Butyl rubber. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection

Avoid contact with skin. Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

WEAR RESISTANT LIQUID (WR) RESIN

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Dark. Grey.
Odour	Slight.
pH	pH (concentrated solution): 7.0 @ 20 °C
Melting point	n/d°C
Initial boiling point and range	>260°C @
Flash point	> 204°C
Vapour pressure	0.03 mmHg @ °C
Relative density	2.80 @ 20 °C°C
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	>300°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong oxidising agents. Strong acids. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Acids - organic. Aldehydes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin contact Irritating to skin. May cause sensitisation by skin contact. The product contains a small amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Irritating to eyes.

WEAR RESISTANT LIQUID (WR) RESIN

Acute and chronic health hazards The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.

Route of entry Inhalation Ingestion. Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity Avoid releasing into the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID label 9

IMDG class 9

ICAO class/division 9

WEAR RESISTANT LIQUID (WR) RESIN

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
----------------	--

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	05/04/2017
Revision	15
Supersedes date	21/05/2015
Risk phrases in full	Not classified. R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

WEAR RESISTANT LIQUID (WR) RESIN

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.