



**SAFETY DATA SHEET  
EPOXY COAT 7000 AR GREY RESIN**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name** EPOXY COAT 7000 AR GREY RESIN

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Resin.

**1.3. Details of the supplier of the safety data sheet**

**Supplier**

ITW Performance Polymers  
Bay 150  
Shannon Industrial Estate  
Co. Clare  
Ireland  
V14 DF82  
353(61)771500  
353(61)471285  
mail@itwpp.com

**1.4. Emergency telephone number**

**Emergency telephone** +44(0)1235 239 670 (24h)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**


**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Chronic 2 - H411

**2.2. Label elements**

**Pictogram**



**Signal word**

Warning

**Hazard statements**

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

## EPOXY COAT 7000 AR GREY RESIN

<b>Precautionary statements</b>	<p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p>
<b>Supplemental label information</b>	<p>EUH205 Contains epoxy constituents. May produce an allergic reaction.</p>
<b>Contains</b>	<p>PHENOL,POLYMER WITH FORMALDEHYDE,GLYCIDYL ETHER, EPOXY RESIN (Number average MW &lt;= 700 )</p>
<b>Supplementary precautionary statements</b>	<p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>PHENOL,POLYMER WITH FORMALDEHYDE,GLYCIDYL ETHER</b>	<b>60-100%</b>
CAS number: 28064-14-4	
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	
<b>TITANIUM DIOXIDE</b>	<b>5-10%</b>
CAS number: 13463-67-7	EC number: 236-675-5
	REACH registration number: 01-2119489379-17-0000
<b>Classification</b> Not Classified	

## EPOXY COAT 7000 AR GREY RESIN

<b>EPOXY RESIN (Number average MW ≤ 700 )</b>		<b>5-10%</b>
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-0000
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411		

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
<b>Inhalation</b>	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
<b>Ingestion</b>	DO NOT induce vomiting. Get medical attention immediately. If swallowed, seek medical advice immediately and show this container or label.
<b>Skin contact</b>	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

#### 5.2. Special hazards arising from the substance or mixture

#### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.
-----------------------------	---

#### 6.2. Environmental precautions

## EPOXY COAT 7000 AR GREY RESIN

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Use only in well-ventilated areas. Handle and open container with care. Keep away from heat, sparks and open flame. Good personal hygiene procedures should be implemented.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup> total dust

**Ingredient comments** No exposure limits known for ingredient(s).

#### EPOXY RESIN (Number average MW <= 700 ) (CAS: 25068-38-6)

##### DNEL

Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day  
Workers - Inhalation; Short term systemic effects: 12.25 mg/m<sup>3</sup>

### 8.2. Exposure controls

**Appropriate engineering controls** Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

**Hand protection** Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The selected gloves should have a breakthrough time of at least 8 hours. To protect hands from chemicals, gloves should comply with European Standard EN374.

**Other skin and body protection** Avoid contact with skin.

## EPOXY COAT 7000 AR GREY RESIN

<b>Hygiene measures</b>	Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.
<b>Respiratory protection</b>	If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Organic vapour filter. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Coloured liquid.
<b>Colour</b>	Grey.
<b>Odour</b>	Slight.
<b>pH</b>	pH (concentrated solution): 7 @ 25 °C
<b>Initial boiling point and range</b>	260°C @
<b>Flash point</b>	204.4°C PMCC (Pensky-Martens closed cup).
<b>Vapour pressure</b>	0.03 mm Hg @ °C
<b>Vapour density</b>	>1
<b>Relative density</b>	1.17 @ °C
<b>Solubility(ies)</b>	Slightly soluble in water.
<b>Auto-ignition temperature</b>	°C
<b>Viscosity</b>	@ °C
<b>9.2. Other information</b>	
<b>Other information</b>	Not available.
<b>Volatility</b>	0
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 0 g/litre.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** Strong oxidising agents. Acids. Amines.

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not available.

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

## EPOXY COAT 7000 AR GREY RESIN

### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with the following materials: Strong oxidising agents. Strong acids. Amines.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

<b>Inhalation</b>	May cause respiratory system irritation. Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.
<b>Ingestion</b>	May cause discomfort if swallowed. Gastrointestinal symptoms, including upset stomach. May cause chemical burns in mouth, oesophagus and stomach.
<b>Skin contact</b>	Irritating to skin. May cause sensitisation by skin contact. The product contains a small amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.
<b>Eye contact</b>	Irritating to eyes.
<b>Acute and chronic health hazards</b>	The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.
<b>Route of entry</b>	Inhalation Ingestion. Skin and/or eye contact
<b>Target organs</b>	Eyes Skin Respiratory system, lungs

## SECTION 12: Ecological Information

**Ecotoxicity** Avoid release to the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Toxicity** Not considered toxic to fish.

### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

### 12.4. Mobility in soil

**Mobility** Do not discharge into drains or watercourses or onto the ground.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** Not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

## EPOXY COAT 7000 AR GREY RESIN

<b>General information</b>	When handling waste, the safety precautions applying to handling of the product should be considered.
<b>Disposal methods</b>	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
<b>Waste class</b>	08 04 99

### SECTION 14: Transport information

**General** No other information known.

#### 14.1. UN number

<b>UN No. (ADR/RID)</b>	3082
<b>UN No. (IMDG)</b>	3082
<b>UN No. (ICAO)</b>	3082

#### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL,POLYMER WITH FORMALDEHYDE,GLYCIDYL ETHER)
<b>Proper shipping name (IMDG)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL,POLYMER WITH FORMALDEHYDE,GLYCIDYL ETHER)
<b>Proper shipping name (ICAO)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL,POLYMER WITH FORMALDEHYDE,GLYCIDYL ETHER)
<b>Proper shipping name (ADN)</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL,POLYMER WITH FORMALDEHYDE,GLYCIDYL ETHER)

#### 14.3. Transport hazard class(es)

<b>ADR/RID class</b>	9
<b>ADR/RID label</b>	9
<b>IMDG class</b>	9
<b>ICAO class/division</b>	9

#### Transport labels



#### 14.4. Packing group

<b>ADR/RID packing group</b>	III
<b>IMDG packing group</b>	III
<b>ICAO packing group</b>	III

#### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**



#### 14.6. Special precautions for user

## EPOXY COAT 7000 AR GREY RESIN

EmS F-A, S-F  
Emergency Action Code •3Z  
Hazard Identification Number 90  
(ADR/RID)  
Tunnel restriction code (E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

Revision date 03/04/2018  
Revision 4  
Supersedes date 04/05/2016  
Hazard statements in full  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.